



Technical Specifications

Power Consumption	0,37 kW
Water Consumption	30 liters/min
Water Pressure bar	3 bar
Net Weight	
Numbers of operators	0

Capacity (standard)*

FISH POCKETS	FISH / KG	FISH / MIN.
45 mm	10–30	250–300
60 mm	4–20	225–300
75 mm	2.5–8.0	200–300
90 mm	2–6	200–275

Technical data to be changed without notice.

*VMK Filleting line

WWW.ARENCO.COM/FISH



- Variable speed
- Distribution funnel for even flow on the VMK Auto Feeder
- Service & Support from VMK
- 0 operators

STANDARD:

- **M9 Single filleting device:**
Splitting device creating single fillets vs. butterfly fillets.
- **M19 Chute:**
For taking care of roe and milt used as delicacy.
- **M24 Belly Cut unit:**
Cleaning out belly cavity of membrane and blood with a rotating grinding stone.
- **M50 Piece cutter:**
Deli-style Herring and more.
- **M60 Steak Cutter:**
Dressed fish prepared to fit in cans.
- **M63 Vacuum nozzle:**
For hygienic evisceration via VMK16
- **M69 Water pump:**
Used to achieve extra water pressure.
- **M95 Sex sorting unit:**
Used for herring to separate females

The VMK Hopper and Elevator is steplessly regulated with a wheel, and consists of plastic carriers that will lift the fish onto a feeder (VMK31) or infeed table for manual feeding. The machine is designed to work with water or brine in the hopper. The elevator can be fitted with different sized buckets depending on the size of fish. It is delivered complete to be placed directly on the floor.

VMK Spare parts and Service: vmk@arenco.com • +46 480 945 00



Arenco AB / VMK Fish Processing
Box 915, SE-391 29 Kalmar
Phone +46 480 945 00
www.vmkfish.com • www.arenco.com/fish
vmk@arenco.com

